

eTRUconnect Truck/Trailer Power Station


Features

30A 480VAC 3P 3W + G
Catalog No: FC30-480-30-35SQP-60
Item No: 2263-100-60



- 1-gang power station for energizing refrigerated truck/trailers, complete with safety-interlocked module and 60' power cord
- Actuator rod allows user to turn on/off and reset tripped breaker
- UL Listed 30A 3P circuit breaker rated 35kAIC @ 480VAC provides short circuit & overcurrent protection
- Cord includes female connector with integral sensor to prove loop is complete before cord can be energized; system "trips" if proving loop is broken (unplugged, cut cord, drive-off, etc.)
- Cord has break-away provisions enabling a technician to re-connect cord after unintentional "drive-off" while still plugged in
- Ultra-bright Green LED indicates female connector is energized
- Type 4X enclosure manufactured from 14GA seam-welded stainless steel (powder-coated light green)
- Factory wired complete to terminal blocks for customer's 480VAC power connection

Drawing



Approvals

- UL 489 Listed / CSA certified molded case circuit breaker

Specifications

Catalog No: FC30-480-30-35SQP-60

Item No: 2263-100-60

Ratings

Female connector	30A 480VAC, 3 phase, 3 wire + ground (IEC 60309-1)
Power cord	600V, 10 gauge, 6 conductor SOOW heavy-duty black cord
Circuit breaker	3P molded case 30A trip, 35,000AIC @ 480VAC with UVR, other trip and AIC ratings available - contact factory
Environmental	Type 4X/IP66
Terminal blocks	Installer wires to terminal blocks: (3) phase & (1) ground pressure type screw terminals: #10 - #6 AWG (5-13mm ²) wire range

Materials

Stainless steel	Enclosure, access cover, module frame, on/off rod, interlock mechanism, and all fasteners
Polyamide	Female connector body, lock ring, cover
Phenolic	Female connector contact carrier
Brass	Female connector contact sleeves
Buna-N (Nitrile/NBR)	O-rings, gaskets

Packaging

Product weight	59 lbs.
Shipping weight	70 lbs.

Options

Pole mount adaptor for 3" or 4" diameter pipe

Replacement Parts

Description	Item No.	Description	Item No.
Safety-interlocked power module	1706-301	Green LED kit	4090-35GNH
60' cord w/female connector	4065-001		